



Product Data Sheet

FK30-SE Calibration Bath

[Print Data Sheet](#)

Product Image



Description

Calibration Refrigerated and Heating Bath for Working Temperatures from -30 to +200 °C

The new calibration baths are perfectly suitable for applications in calibration laboratories and conform to the requirements specified by DIN ISO 9001:2000. The instruments provide highest temperature stability to ± 0.005 °C and temperature uniformity better than ± 0.01 °C. An optional precision reference sensor with integrated measuring electronics and RS232 connection is available.

Advantages

- o VFD COMFORT DISPLAY, resolution 0.01 °C
- o Keypad for setpoints, warning/safety values and menu functions
- o ICC (Intelligent Cascade Control), self-optimizing temperature control
- o ATC3 3-Point-Calibration
- o Pt100 External sensor connection for measurement and control
- o SMART PUMP, electronically adjustable pump stages
- o Adjustable high temperature cut-out, visible via display
- o RS232 interface for online communication
- o Integrated programmer for 10 program steps
- o Highest temperature stability to ± 0.005 °C
- o Temperature uniformity better than ± 0.01 °C
- o Optional Pt100 sensor for reference temperature measurements
- o Temperature chamber with overflow at maximum liquid level
- o Active Cooling Control

Order Information

Model: FK30-SE

Order no.: 9250627

Available mains power:
230V / 50Hz
115V / 60Hz

Similar Models

These models could also be interesting for you:

FK31-SE

Sales & Support:

+49 7823 51-190

Monday to Friday
7:30 am - 17:00 pm

JULABO Labortechnik GmbH
Eisenbahnstrasse 45
77960 Seelbach/Germany
Phone +49 7823 51-0
Fax +49 7823 2491
info@julabo.de
www.julabo.de

Technical changes reserved.
Pictures may differ from original.

Technical Specifications

Working temperature range	-30 ... 200 °C			
Temperature control	ICC			
Temperature stability	± 0.005 °C			
Display	VFD			
Display resolution	0.01 °C			
Integrated programmer	available			
Heater capacity	2000 W			
Cooling capacity	20	0	-20	°C
	460	340	150	W
Refrigerant	R134a			
Pump capacity	Pressure: 700 mbar Suction: 400 mbar Flow rate: 22-26 l/min			
Digital interfaces	RS232, optional Profibus			
External Pt100 sensor connection	available			
Bath opening / bath depth (W x L / D)	Ø = 12 / 17 cm			
Filling volume	14 Liters			
Dimensions (W x L x H)	32 x 45 x 79 cm			
Weight	33 kg			
Ambient temperature	5...40 °C			
Classification according to DIN 12876-1	3 (FL)			

Miscellaneous

Removable venting grid for convenient cleaning to maintain cooling performance. Including bath cover with 6 openings